



Technical Data	GW15K-DT	GW17K-DT	GW20K-DT	GW25K-DT
DC Input Data				
Max. allowed PV Power [W]	19500	22100	26000	32500
Nominal DC Power [W]	15400	17500	20500	25800
Max. DC voltage [V]	1000	1000	1000	1000
MPPT voltage range [V]	260~850	260~850	260~850	260~850
Starting voltage [V]	250	250	250	250
Max. DC current [A]	22/22	22/22	22/22	27/27
No. of DC connectors	4	4	4	6
No. of MPPTs	2 (can parallel)	2 (can parallel)	2 (can parallel)	2 (can parallel)
DC connector	MC4/ Phoenix/ Amphenol			
AC Output Data				
Nominal AC power [W]	15000	17000	20000	25000
Max. AC power [W]	15000	17000	20000	25000
Max. AC current [A]	25	25	30	37
Nominal AC output	50/60Hz; 400Vac			
AC output range	45~55Hz/55~65Hz; 310~480Vac			
THDi	<1.5%			
Power factor	0.8 leading~0.8 lagging			
Grid connection	3W/N/PE			
Efficiency				
Max. efficiency	98.2%	98.2%	98.4%	98.4%
Euro efficiency	>97.7%	>97.7%	>98.1%	>98.1%
MPPT adaptation efficiency	99.9%	99.9%	99.9%	99.9%
Protection				
Residual current monitoring unit	Integrated			
Anti-islanding protection	Integrated			
DC switch	Integrated (optional)			
AC over current protection	Integrated			
Insulation monitoring	Integrated			
Certifications & Standards				
Grid regulation	VDE-AR-N4105, AS4777.2/3, IEC61727, VDE0126-1-1, EN50438, NRS097-2-1, G59/3, ERDF-NOI-RES_13E;		AS4777.2/3, En50438, VDE-AR-N 4105, VDE0126-1-1, MEA&PEA, G59/3, NRS097-2-1, IEC61727, ERDF-NOI-RES_13E	VDE-AR-N 4105, IEC61727, VDE0126-1-1, EN50438, G59/3;
Safety	IEC62109-1&-2, AS3100			IEC62109-1&-2
EMC	EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 61000-3-11, EN 61000-3-12			
General Data				
Dimensions (WxHxD) [mm]	516*650*203			
Weight [kg]	39			40
Mounting	Wall bracket			
Ambient temperature range	-25~60°C (>45°C derating)			
Relative humidity	0~95%			
Max. operating altitude	4000m(> 3000m derating)			
Protection degree	IP65			
Topology	Transformerless			
Night power consumption [W]	<1			
Cooling	Fan cooling			
Noise emission [dB]	<45			
Display	5.0" LCD			
Communication	Wi-Fi; RS485 or Ethernet			
Standard warranty [years]	5/10/15/20/25 (optional)			